

vjet[®]1200

Thermal Inkjet Coder



“An ultra versatile thermal inkjet coder adaptable to your printing needs.”



vjet[®]1201



vjet[®]1202



vjet[®]1204

Mylan[®]
GROUP
Formulating a Greener World[®]

MYLAN GROUP
Longduc Industrial Park, Travinh City, Travinh Province, Vietnam
Tel: +84 743 846 997 - Fax: +84 743 846 998
Email: info@mylangroup.com - Website: www.mylangroup.com

Inkjet
Technology by 

VJETSTORE
No. 1.2, Floor 1, Block A Phu Hoang Anh, Section 1
Nguyen Huu Tho Street, Phuoc Kien Ward
Nha Be District, Ho Chi Minh City, Vietnam
Tel: +84 837 817 990 - Fax: +84 837 840 998
Email: info@vjetstore.com - Website: www.vjetstore.com

VJET®1200 THERMAL INKJET CODER

Features

Touch Screen	12" capacitive touch screen
Languages Support	Multi languages (English - default, Chinese, German, Japanese, Korean, Vietnamese...)
Free Template Design	Powerful template design with PC software
Font	Windows True Fonts
Database Support	SQL, ACCESS, EXCEL, TEXT, etc.
Barcode Support	CODE 11, CODE 2OF5 STANDARD, CODE 2OF5 INTERLEAVED, CODE 2OF5 IATA, CODE 2OF5 MATRIX, CODE 2OF5 DATA LOGIC, CODE 2OF5 INDUSTRY, EAN8, EAN13, UPC12, UPCA, UPCE, CODE 39, CODE 39 EXTENDED, EAN UCC128, CODABAR 2, CODE 128, GS1 DATABAR EXPANDED, GS1 DATAMATRIX, UCC128, QR CODE, DATAMATRIX, GS1 DATABAR EXPANDED STACKED, GS1 128, QR CODE 2005
Receive Data from 3rd Party Devices	USB 2.0, Ethernet RJ45 port

Technical parameters

Printing Technology	HP TIJ2.5 (Hewlett Packard Thermal Inkjet)
Printable Heights	Vjet®1201: 1~12.7mm (supports up to 4 head) Vjet®1202: 1~25.4mm (supports up to 2 head) Vjet®1204: 1~50.8mm (supports only 1 head) * Maximum cartridges supported: 4
Printing Objects	Alphanumeric, Logos, Date/Time, Expiry date, Julian date, Shift Code, Counter/Box Lot, and Barcode
Printing Speed	30 m/min @ 600 dpi 92 m/min @ 300 dpi
Resolution	Up to 600 dpi x 600 dpi
Density	3 levels
Throw Distance	1~5mm
Operation Interface	PC software on 12" touch screen
Port	Ethernet 100 Mbps port USB 2.0 DP15 I/O Photo sensor port Encoder port
Ink Management	Automatic recognition the ink type (aqueous or solvent) and adjustment of printing parameters Automatic nozzle_switching and cleaning of cartridges to extend lifetime Ink consumption calculator
Ink Solution	HydraJET®2016, HydraJET®2020, HydraJET®2030 series - Aqueous ink for porous, semi-porous media and food SolJET®2701, SolJET®2704, SolJET®2705 series - Solvent ink for semi and non-porous media Supports various colors of ink: Black, Red, Green, Blue Supports ink delivery system inkFeeder used to feed the ink to cartridges. Supports volume: 35ml, 42ml, 400ml (bulk) and 700ml (bulk)
Mounting	Controller: with mounting bracket, 90° degree rotation support Print head: anti-shock mechanism, supports side by side and upside down printing directions
Power Supply	AC 100V-240V, 50/60Hz, 2.0A, Max consumption: 138W
Operating Environment	5-60°C and 90% air humidity, non-condensing
Warranty	12 months limited warranty
Dimensions (mm)	

